Advantage LX Desktop Thermal Printer











Advantage LX

Mission-critical desktop printer.

CognitiveTPG's most popular desktop label printer, the Advantage LX (formerly known as the Blaster or Blazer), is still the preferred industry choice for mission-critical desktop printer applications. It remains a much beloved printer by both its users and our resellers.

Programming

CognitiveTPG's advanced firmware command language, CPL, is so easy to use that programming it into any application is a snap.

Upgrading

The use of flash memory allows for easy firmware upgrades to get you the latest features available for your printers.

Capacity

Store hundreds of objects with our expanded memory. With 4 MB of flash memory in every printer, you have plenty of room to add fonts, graphics, and programming.

Size

Why settle? Now you can save valuable time and space with high-performance printing in a small footprint.

Durability

The Advantage LX is the only desktop thermal printer that has a full metal mechanism and a proven track record. As one of the most rugged printers in the marketplace, the Advantage LX thrives in the harshest environments where others have failed.

Reliability

A good, simple design and strong foundation make our printers some of the most reliable in the field. When productivity is critical, you can count on the Advantage LX.



Advantage LX Mission-Critical Desktop Printer

2" AND 4" MODELS

Technical Specifications

	2" Model	4" Model
PRINT		
Method	Direct Thermal or Thermal Transfer	Direct Thermal or Thermal Transfer
Width (max)	2.2" (56 mm)	4.1" (104 mm)
Length (max)	40" (1,016 mm)	20" (513 mm)
Speed (max)	3 ips (76 mm/sec)	3 ips (76 mm/sec)
Resolution	203 dpi (8 dpmm)	203 dpi (8 dpmm)
MEDIA		
MEDIA Width	1" - 2.4" (25 mm - 61 mm)	2" - 4.3" (50mm - 109mm)
Roll Diameter	4.7" (119 mm)	4.7" (119 mm)
Ribbon Length (TT models only)	3150" (80 m)	3150" (80 m)
Indexing	Black bar, notch, and gap	Black bar, notch, and gap
BAR CODES	21 standard bar codes, including Add2, Add5, Codabar, Code39, Code93, Code 128A/B/C, D2of5, 2of5, S2of5, EAN8/8+, EAN13/13+, EAN128, Maxicode, MSI/I1, PDF417, Plessey, Postnet, UPCA/A+/E/E1	
FONTS		
Bitmapped	7 styles with up to 10x10 magnification, variable boldn	ess and spacing
International	Sans serif font in 7 pt. sizes, up to 4x4 magnification, variable boldness and spacing	
Scalable Smooth Fonts	3 Ultra Font styles for smooth characters in any size and boldness	
Rotataions	0, 90, 180, 270 degrees	
GRAPHICS	PCX and BMP formats	PCX and BMP formats
MEMORY*	RAM - 8 MB, Flash - 4 MB	RAM - 8 MB, Flash - 4 MB
COLUMN II CATION C	<u> </u>	
COMMUNICATIONS	Serial (DB9)	Serial (DB9), Parallel (1284B)
	Parallel (1284B)	Serial (DB9), Parallel (1284B), Ethernet
	Serial (DB9), Ethernet	
ELECTRICAL*	Auto-ranging 100-240VAC, 50-60 Hz, 24 VDC Output	Auto-ranging 100-240VAC, 50-60 Hz, 24 VDC Output
ENVIRONMENTAL	Operates at 41°F to 104°F (5°C to 40°C)	Operates at 41°F to 104°F (5°C to 40°C)
DIMENSIONS		
Width	5.0" (127 mm)	6.8" (173 mm)
Height	6.1" (155 mm)	6.1" (155 mm)
Depth	9.4" (238 mm)	9.4" (238 mm)
·		
WEIGHT (DT / TT)	3.1 lbs. (1.41 kg) / 3.9 lbs. (1.77 kg)	3.9 lbs. (1.77 kg) / 4.4 lbs. (2.0 kg)
ACCESSORIES		
Standard	Quick Start Guide, power supply and cord (cord included only in LBxxx-2xx3-01x models)	
Downloads from Web site	Windows drivers, programmer's guide, NiceLabel design software, and User's Guide	
Optional	Communications cables, label (peeler) dispenser, Ethernet, real-time clock	
WARRANTY		
Printer	24 months from data of nurchase (requires registration	and excludes printhead)
1 11111.001	24 months from date of purchase (requires registration and excludes printhead)	
PROGRAMMING LANGUAGE	Cognitive Programming Language (CPL)	Cognitive Programming Language (CPL)

*specifications for Advantage LX printers with S/N's starting with "L"



25 Tri-State International, Suite 200, Lincolnshire, IL 60069

Toll Free: 800-732-8950 Phone: 847-383-7900 Fax: 847-383-7949

www.CognitiveTPG.com

Copyright 2008 CognitiveTPG. All Rights Reserved.

